


















مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 DH-HAC-HFW2802TP-Z-A NEW Product	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.7-11mm motorized lens Max Aperture: F1.5 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		18,900,000
2 DH-HAC-HFW2802TP-A-I8 NEW Product	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		12,800,000
3 DH-HAC-HFW2802EP-A NEW Product	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 40m, Smart IR IP67, DC12V±30%		11,000,000
4 DH-HAC-HFW2601TP-Z-A NEW Product	6MP WDR HDCVI IR Bullet Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 2.7-13.5mm motorized lens Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		14,800,000
5 DH-HAC-HFW2601EP-A NEW Product	6MP WDR HDCVI IR Bullet Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 40m, Smart IR IP67, DC12V±30%		9,950,000








مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
6	DH-HAC-HFW1400RP-VF-IRE6 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm vari-focal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		9,500,000
7	DH-HAC-HFW1400DP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		6,750,000
8	DH-HAC-HFW1400BP 1/3" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		6,350,000
9	DH-HAC-HFW1400SP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		5,330,000
10	DH-HAC-HFW1400TP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 25m, Smart IR IP67, DC12V		5,150,000
11	DH-HAC-ME1400B-PIR 4MP HDCVI MotionEye Camera 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110° detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		5,970,000
12	DH-HAC-HFW2231RP-Z-IRE6 1/2.8" 2.1Megapixel CMOS, (Starlight) 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Motorized lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		13,200,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
13 DH-HAC-HFW2231EP	<p>1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 40m, Smart IR IP67, DC12V</p>		8,300,000
14 DH-HAC-HFW2231DP	<p>1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V</p>		8,900,000
15 DH-HAC-HFW1220RP-VF-IREC	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR IP67, DC12V</p>		7,760,000
16 DH-HAC-HFW1220DP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>		5,080,000
17 DH-HAC-HFW1220BP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		4,750,000
18 DH-HAC-HFW1220SP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		3,910,000
19 DH-HAC-HFW1200DP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>		4,810,000








توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
20	DH-HAC-HFW1200BP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 50m, Smart IR IP67, DC12V		4,500,000
21	DH-HAC-HFW1200SP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		3,780,000
22	DH-HAC-HFW1200SLP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		3,100,000
23	DH-HAC-HFW1200TP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 25m, Smart IR IP67, DC12V		3,500,000
24	DH-HAC-HFW1200RMP-0360B Metal Case	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		3,240,000
25	DH-HAC-ME1200BP-PIR	2MP HDCVI MotionEye Camera 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		4,400,000
26	DH-HAC-HUM1220AP	2MP HDCVI MotionEye Camera 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR , Support OSD Menu 12m/100°detecting range/angle Two level(jumper) detection sensitivity adjustable Built-in tamper switch DC12V		5,600,000








ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
27	DH-HAC-HUM3201B	1/2.8" 2Megapixel CMOS(Starlight) 25/30fps@1080P, 25/30fps@720P 2.8mm fixed lens HD and SD output switchable WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR , Support OSD Menu DC12V		7,420,000
28	DH-HAC-HFW1100RP-VF	1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.7~12mm vari-focal lens Max. IR LEDs length 30m, Smart IR IP67, DC12V		3,750,000
29	DH-HAC-HFW1100SP	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		2,400,000
30	DH-HAC-HFW1100SL	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		1,950,000
31	DH-HAC-HFW1100RMP-0280B Metal Case	1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.8mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V		1,990,000
32	DH-HAC-HFW1100RMP-0360B Metal Case	1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V		1,990,000
33	DH-HAC-HFW1100RP	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V		1,820,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
34 DH-HAC-HDW2802TP-A NEW Product	4K Starlight HDCVI IR Eyeball Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 50m, Smart IR IP67, DC12V±30%		11,000,000
35 DH-HAC-HDW2601TP-Z-A NEW Product	6MP WDR HDCVI IR Eyeball Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 2.7-13.5mm motorized lens Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 60m, Smart IR IP67, DC12V±30%		14,800,000
36 DH-HAC-HDW2601TP-A NEW Product	6MP WDR HDCVI IR Eyeball Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 50m, Smart IR IP67, DC12V±30%		9,950,000
37 DH-HAC-HDBW1400RP-VF	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Varifocal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, IK10, DC12V		9,500,000
38 DH-HAC-HDW1400EMP-A 	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable Built-in Mic OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		5,850,000
39 DH-HAC-HDW1400EMP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		5,500,000






توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
40 DH-HAC-HDW1400MP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		5,100,000
41 DH-HAC-HDBW2231FP	1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, IK10, DC12V		8,600,000
42 DH-HAC-HDW2231EMP	1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67,DC12V		8,300,000
43 DH-HAC-HDBW1220RP-VF	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V		7,240,000
44 DH-HAC-HDW1220EMP-A	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens Built-in Mic HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V		4,100,000
45 DH-HAC-HDW1220MP	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		3,500,000
46 DH-HAC-HDW1200LP	2MP HDCVI IR Eyeball Camera 1/2.7" 2Megapixel CMOS Max 30fps@1080P 2.1mm fixed lens HD and SD output switchable Built in Mic Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR IP67, DC12V		5,360,000






توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
47	DH-HAC-HDW1200MP	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		3,400,000
48	DH-HAC-HDW1200EMP-A Metal Case	1/2.7" 2Megapixel CMOS 25/30fps@1080P Built-in MIC Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens (6mm optional) Max. IR LEDs length 50m, Smart IR IP67, DC12V		4,000,000
49	DH-HAC-HDW1100MP-0360B	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		1,870,000
50	DH-HAC -HDW1100RP-0360B	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V		1,820,000
51	SD22204I-GC	Powerful 4x optical zoom (2.7mm~11mm) Max. 25/30fps@1080P, 50/60fps@720P resolution WDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC Max 100°/s pan speed HD & SD Switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern IP66, IK10, OSD		14,250,000
52	DH-SD59225I-HC-S2	1/2.8" 2Megapixel Exmor R CMOS (Starlight) Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out 1 Audio Input , RS485 IR Distance up to 150m IP66,OSD		59,800,000
53	SD59230I-HC	2MP 30x Starlight IR PTZ HDCVI Camera 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720PResolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 Built-in 2/1 Alarm in/out IR Distance up to 150m IP66,OSD		7,800,000






توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
54 DH-SD49225I-HC	<p>2MP 25x Starlight IR PTZ HDCVI Camera 1/2.8" STARVIS CMOS Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720P Resolution 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern 2/1 Alarm In/Out 1CH Audio In RS485 IR Distance up to 100m IP66,OSD</p>		44,000,000
55 DHI-XVR4104HS-S2	<p>4CH Penta-brid 1080N/720P Real-Time Recorder H.264 video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 Megapixel(20 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		6,190,000
56 DHI-XVR5104HS-S2	<p>4CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		8,700,000
57 DHI-XVR5104HS-4M	<p>4CH Penta-brid 4MP Non-real Time , 1080P Real-Time Recorder H.264+/H.264 dual-stream video compression 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI(2K) ,1* VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		12,000,000
58 DH-XVR5104HS-4KL-X	<p>4CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265 dual-stream video compression 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 8 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100 Mbps LAN Interface P2P Support</p>		12,870,000





توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
59	<p>DHI-XVR4108HS-S2</p> <p>8CH Penta-brid 1080N/720P noneReal-Time Recorder H.264 video compression 8CH: 1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 Megapixel(40 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		8,300,000
60	<p>DHI-XVR5108HS-S2</p> <p>8CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 5 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		13,700,000
61	<p>DH-XVR5108HS-X</p> <p>NEW Product</p> <p>8CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100 Mbps LAN Interface P2P Support</p>		14,480,000
62	<p>DHI-XVR5108H-4KL</p> <p>8CH Penta-brid 4K Recorder 4K@7fps, 4MP@15fp , 1080P/720P@25fps H.264+/H.264 dual-stream video compression 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface P2P Support</p>		18,200,000
63	<p>DH-XVR5108H-4KL-X</p> <p>NEW Product</p> <p>8CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265 dual-stream video compression 1/4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface P2P Support</p>		19,400,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفن داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.



مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
64	<p>DHI-XVR4116HS-S2</p> <p>8CH Penta-brid 1080N/720P noneReal-Time Recorder H.264 video compression 16CH: 1/4/9/16 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 5 Megapixel(72 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		14,800,000
65	<p>DH-XVR5116H-X</p> <p>NEW Product</p> <p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		24,500,000
66	<p>DH-XVR5216AN-S2</p> <p>16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface P2P Support</p>		26,500,000
67	<p>DH-XVR5216AN-X</p> <p>NEW Product</p> <p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		28,500,000
68	<p>DHI-XVR5216AN-4KL</p> <p>16CH Penta-brid 4K Recorder 4K@7fps, 4MP@15fp , 1080P/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface P2P Support</p>		35,000,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

69 DH-XVR5216AN-4KL-X	<p>16CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultanous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		38,000,000
70 DH-XVR5416L	<p>16CH Penta-brid 1080N/720P Real-Time,1080P None-Real time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 6 TB 1 e-SATA 2*HDMI , VGA , TV simultanous video Output RS485 , RS 232 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface P2P Support</p>		52,000,000
72 DH-HCVR8816S-S3	<p>All channel 1080P realtime recording Support HDCVI/AHD/Analog/IP Video input H.264 dual-stream video compression 16 channel synchronous realtime playback Tribrid (IP+CVI+Analogue)N+M[16+48 up to 12Megapixel(384Mbps)] 16 Audio Input , 1 Audio Output 16*Alarm Input , 6*Relay Output 8 SATA ports, up to 64TB, 1 eSATA 2 HDMI(HDMI1 up to 4K), 1 VGA, 1 TV HDMI 1/VGA simultaneous video output,HDMI2/VGA(HDMI1) independent video output RS485 , PTZ Support 4 ports (2 Rear USB3.0, 2 Front USB2.0) 2*10/100/1000 Mbps LAN Interface IVS: Tripwire, Intrusion, Abandoned/Missing, Scene Change, Face Detection, People Counting, Smart Tracking P2P Support</p>		Call
73 DH-XVR5232AN-S2	<p>32CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH:1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [32 IP up to 5 Megapixel(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB HDMI , VGA , 1TV video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface P2P Support</p>		46,000,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
74 DH-XVR5232AN-X NEW Product 	32CH Penta-brid 1080P Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 6 Megapixel(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support		48,800,000
75 DH-XVR5432L 	32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support		84,000,000
76 DH-XVR5832S 	32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 16 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 8 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 2 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support		98,000,000
77 PFT2100	HDMI-HDCVI Converter *Input HDMI video signal, self-adaptive output HDCVI signal *HDMI support mode, 1024*768@60Hz, 1280*720@50/60Hz, 1280*1024@60Hz,1600*1200@60Hz, 1920*1080@50/60Hz *HDCVI output format, 720P/50, 720P/60, 1080P/25, 1080P/30 *Output Cable Length 1080P: 75-5 coaxial cable support 300m/720P: 75-5 coaxial cable support 500m *Power:DC12V		6,400,000
78 TP2105	HDCVI Video Converter real time non-compression transmission *Input: 1*HDCVI (BNC) *Output: 1*HDCVI (BNC), 1*CVBS (BNC), 1*HDMI, 1*VGA *1080p/720p: 75-5 coaxial support 100m Input Transmission Distance *1080p/720p: 75-5 coaxial support 100m HDCVI Output Transmission Distance *Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s *RS485		6,800,000
79 PFM801	*1 Channel HDCVI Transmission Signal *720P, 400M(max); 1080P, 200M(max)Transmission Distance *Input voltage DC24-36V, can provide DC12V8W(max) power supply to remote cameras *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal and 1-ch DC power *Excellent anti-thunder, anti-static and anti-interference capabilities *Compatible with HDCVI/TVI/AHD format		770,000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
80 DH-PFM900-E	<p>4" IPS screen and QWERTY flip keyboard with 45keys</p> <p>Support H.264/H.265 HD decoding protocol</p> <p>Support IP,HDCVI/AHD/TVI/CVBS</p> <p>Support IP configuration via Onvif protocol</p> <p>Support audio and RS485 control</p> <p>Support TDR network cable test and digital multi-meter function</p> <p>Support PoE+, DC12V/2A power out;</p> <p>Replaceable 7.4V/22.2Wh polymer lithium ion battery , which can last 8 hours for normal use;</p> <p>Compatible with more than 30 PTZ protocols(Pelco-D/P, Samsung, Panasonic, Lilin, Yaan,...)</p> <p>Dual LED flashlight</p>		52,000,000
81 DH-PFM905-E	<p>4" IPS display, 800*480 resolution, 16.7M colors</p> <p>Support HDCVI/AHD/TVI/CVBS</p> <p>Support RS485 PTZ control</p> <p>Support audio test and digital multi-meter function</p> <p>Support DC12V/1A power out</p> <p>Dual LED torch light</p> <p>Replaceable 7.4V/10.4Wh polymer lithium battery , which can last 5 hours for normal use</p>		26,000,000

EXCLUSIVE AGENT OF MAXRON, Dahua, Tiandy, ALBATRON, OPTINA, SENTRY

